

AQ-1000 Features & Options

STANDARD WASHER WITH STATIONARY

STAINLESS STEEL SPRAY ARMS

Standard Features:

- Double Wall Stainless Steel Chamber
- Stainless Steel Spray Arms
- Variable Wash Time Cycles (3, 5, or 7 Minute)
- Wash and Rinse Cycles
- Automatic Chemical Injection
- LCD Status Display
- Heavy-Duty Caster Wheels
- Fill & Drain Hose Set
- 1 HP Motor/ Stainless Steel Pump
- 115 Volt, 20 Amp AC Operation

Optional Features:

- Disinfectant Application System
- Oscillating Spray Arms
- Utility Wash Trays
- Front Door Window
- Air Dry Blower
- 1.5 HP Motor Upgrade/ Stainless Steel Pump
- 230V, 50/60Hz, Single Phase AC Operation



Total Outer Dimensions

• Width 33-1/2"

• Length 64"

• Height 62"

Effective Chamber Dimensions

Width 26-1/2"Length 51-1/4"Height 41-1/2"

Like all Aqua Phase models, in order to operate the machine once the unit is located, all you need to do is hook up two hoses — one for the hot water fill and one for the drain, connect the Aqua Phase to an appropriate power source and begin saving time, improving efficiency and enhancing your infection control protocol.