# AQ-4800HTFeatures & Options

# **BARIATRIC WIDTH WASH CHAMBER**

#### **Standard Features:**

- Double Wall Stainless Steel Chamber
- Stainless Steel Spray Arms
- Oscillating Spray Arms
- Ramp Set (2 @ 4-ft each)
- Variable Wash Times
- Wash and Rinse Cycles
- **Automatic Chemical Injection**
- LCD Status Display
- Front Door Window
- Heavy-Duty Caster Wheels
- Adjustable Leveling Feet
- Fill & Drain Hose Set.
- 2 HP Motor/ Stainless Steel Pump
- 230V, 50/60Hz, Single Phase AC Operation

### **Optional Features:**

- Disinfectant Application System
- Entry/Exit Doors-Pass Through Model
- Conveyor Floor Transfer System
- **Utility Wash Trays**
- **Electronic Temperature Monitor**
- Pump Motor Upgrade 3 HP
- Extended Ramp Sets
- Operations Validation System (Including Printed Performance Records)

## **Total Outer Dimensions**

Width 74"

Length 108-3/4"

Height 101"

Height 74-1/4"

Effective Chamber Dimensions Width 51" Length 105-3/8"

Like all Aqua Phase models, in order to operate the machine once the unit is located, all you need to do is hook up two hoses — one for the hot water fill and one for the drain, connect the Aqua Phase to an appropriate power source and begin saving time, improving efficiency and enhancing your infection control protocol.